

NEW 2026

BRUTE FORCE® 300



MSRP
\$5,199

- GRAYISH BLUE
- FIRECRACKER RED



POWER		Starting System	Electric
Engine	4-stroke, single-cylinder, SOHC, liquid-cooled	Fuel Capacity	3.2 gal
Displacement	271cc	Steering	Conventional tie-rod
Bore x Stroke	72.7 x 65.2mm	Turning Radius	9.2 ft
Compression Ratio	10.6:1	Towing Capacity	500 lb
Maximum Horsepower	21.0 hp ¹ @ 7,500 rpm	Total Rack Capacity	110 lb
Maximum Torque	16.2 lb-ft @ 6,500 rpm	Rack Capacity, Front/Rear	44/66 lb
Fuel System	FI with 32mm throttle body	Lighting	LED headlights, LED handlebar mounted light, Halogen taillight
Ignition	DC-CDI	DETAILS	
Transmission	Automatic Continuously Variable Transmission (CVT) with centrifugal clutch (H,L,N,R)		
Final Drive	2WD, shaft	Frame Type	Double-cradle, tubular steel
CAPABILITY		Tread Width	33.5/32.7 in
Front Suspension / Wheel Travel	Double wishbone, adjustable spring preload/5.3 in	Overall Length	75.4 in
Rear Suspension / Wheel Travel	Swingarm with single shock, adjustable spring preload/5.5 in	Overall Width	42.5 in
Front Tire	Maxxis® AT 22 x 7-10	Overall Height	46.1 in
Rear Tire	Maxxis® AT 22 x 10-10	Seat Height	33.3 in
Front Brakes	Dual 180mm discs	Estimated Dry Weight	527.0 lb** / 529.2 lb** CA Model
Rear Brakes	Single 180mm disc	Curb Weight	551.3 lb* / 553.5 lb* CA Model
Ground Clearance	6.1 in	Wheelbase	45.9 in
		Instruments	Speedometer, tachometer, gear position indicator, fuel gauge, clock, odometer, hour meter, trip meter, etc.
		Color Choices	Grayish Blue, Firecracker Red

Scan with camera to view videos, key features and more.



^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.